



# S29937

12T8/LED/48-850/DR  
12W T8 LED; Medium bi-pin base; 5000K; 50000 Average rated hours; 1800 Lumens; Type A; Ballast dependent



### Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required\*
- Solid State LED lighting
- High efficacy
- DLC Listed
- All glass tube

\*May not be compatible with every ballast. Refer to the ballast compatibility chart.

S29937

Ballast required.

View:

[Ballast Compatibility Chart](#)

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S29937	045923299377	12	25W-32W	T8	Medium Bi-Pin	G13	12T8/LED/48-850/DR
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
Non-Dimmable	Gloss White	48"	1.00"	1800	50000	5000	Natural Light
CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:	RoHS Compliant
82	210	-20C (-4F) to a maximum of +45C (+113F)	10	Box	Lawful for sale in California	PL37S18SFPDE <a href="#">DLC Search</a>	Yes
UL or ETL Listed			UL Classification			Warranty	



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

